Product: EPOXY A



Safety Data Sheet prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier

EPOXY A

Revision Date:

07/05/2016

Product Name:

EPOXY Part A

Supercedes Date: 07/05/2016

1.2 Relevant identified uses of the substance or mixture and uses advised against

Base of 2 component adhesive. For use by appropriately trained applicators.

1.3 Details of the supplier of the safety data sheet

Manufacturer:

American Traffic Products, Inc 1450 N Fitzgerald Ave

Rialto, CA 92376

909-356-2130

1.4 Emergency telephone #:

CHEMTREC 1-800-424-9300 (Inside US)

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Eye Irritation, category 2 Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word Warning

Named Chemicals on Label

reaction product: bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)

HAZARD STATEMENTS

Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
PRECAUTION PHRASES		
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P391	Collect spillage.

2.3 Other hazards

Not applicable

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	Chemical Name		<u>%</u>
25068-38-6	reaction product: bisphenol-a-(epich molecularweight <= 700)	lorhydrin) epoxy resin (number average	50-75
14807-96-6	talc		10-25
13463-67-7	titanium dioxide		2.5-10
CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
25068-38-6	GHS07-GHS09	H315-317-319-411	0
14807-96-6			0
13463-67-7			0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name reaction product: bisphenol-a-(epichlorhydrin)

% OSHAPEL ACGIH TLV

epoxy resin (number average molecularweight

<= 700)

10-25 2.0 mg/m3

50-75

talc titanium dioxide

2.5-10 15.0 mg/m3

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Rubber or plastic gloves. Long sleeved clothing. Remove and wash contaminated clothing before reuse. Rubber or plastic apron.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:

Not determined

Physical State

Liquid

Faint epoxy odor

Odor threshold

Not determined

pH

Odor

Non-aqueous

Not determined

Melting point / freezing point (°C)

Boiling point/range (°C)

N.D. - N.D.

Flash Point, (°F / °C)

>240F / >116C

Evaporation rate

Not determined

Flammability (solid, gas)

Not determined

Upper/lower flammability or explosive

limits

N/A - N/A

Vapour Pressure

Not determined

Vapour density

Not determined

Relative density

Not determined

Solubility in / Miscibility with water

Negligible

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity

35,000 - 50,000 cps

Date Printed: 07/05/2016

Product: EPOXY A

Explosive properties

Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/I:

0

Specific Gravity (g/cm3)

1.422

Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. StableStable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50:

Inhalation LC50:

Irritation:

No information available.

Corrosivity:

No information available.

Sensitization:

No information available.

Repeated dose toxicity:

No information available.

Carcinogenicity:

No information available.

Mutagenicity:

No information available.

Toxicity for reproduction:

<= 700)

No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.

Chemical Name

Oral LD50

Dermal LD50

Vapor LC50

25068-38-6

reaction product: bisphenol-a-(epichlorhydrin)

epoxy resin (number average molecularweight >2000 mg/kg, rat, oral

>2000 mg/kg, rat

13463-67-7 titanium dioxide

10000 mg/m3, oral (rat)

Additional Information:

This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

101	
12.1	Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

LC50 96hr (fish):

No information

No information

No information

12.2 Persistence and degradability:

No information

12.3 Bioaccumulative potential:

No information

12.4 Mobility in soil:

No information

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects:

No information

CAS-No. Chemical Name

Chemical Name

EC50 48hr

IC50 72hr

LC50 96hr

Product: EPOXY A

25068-38-6

reaction product: bisphenol-a-(epichlorhydrin)

epoxy resin (number average molecularweight No information <= 700)

No information

1.5-7.7 mg/L

14807-96-6

talc

No information

OECD202)ation

No information

13463-67-7

titanium dioxide

>100 mg/l (EC50, 48h, Daphnia magna

na No information

>1000 mg/l

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN	number

UN3082

14.2 UN proper shipping name

Technical name

Environmentally Hazardous Substance, Liquid, N.O.S. reaction product: bisphenol-a-(epichlorhydrin) epoxy resin

14.3 Transport hazard class(es)

14.6 Special precautions for user

Subsidiary shipping hazard

14.4 Packing group

...

III

9

14.5 Environmental hazards

For professional use only.

EmS-No.:

F-A, S-F

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:

Not applicable

EPA VOC Content Limit (g/l):

N/A

Product VOC Content (g/l)

_

Thinning Recommendations:

N/A

Application Recommendations:

* As per the federal EPA definition for coating categories in 40 CFR 59.401.

** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name

CAS-No.

alumina trihydrate

21645-51-2

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

California Proposition 65:

Warning: The following ingredients present in the product are known to the State of California to cause cancer:

Chemical Name

CAS-No.

titanium dioxide

13463-67-7

Warning: The following ingredients present in the product are known to the State of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Reasons for revision

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark ESIS (The European Chemical Substances Information System), provided by the European Commission Joint Research Centre in Ispra, Italy

Annex VI of the EU Council Directive 67/548/EEC

Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation)

EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission EU European Union United States US

CAS Chemical Abstract Service EINECS

European Inventory of Existing Chemical Substances Registration, Evaluation, Authorization of Chemicals Regulation REACH

Globally Harmonized System of Classification and Labeling of Chemicals GHS

LTEL Long term exposure limit Short term exposure limit STET. OEL Occupational exposure limit

Parts per million ppm

ma/m3 Milligrams per cubic meter

TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits VOC Volatile organic compounds

g/1Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.